



قابلیت های هوشمند:

- تشخیص حرکت
- جستجوی رفتار

- ورودی 16 کانال آنالوگ و 8 کانال آی پی
- قابلیت فشرده سازی صدا

- پشتیبانی از فشرده سازی تصویر H.265
- پشتیبانی از پروتکل های RTSP و ONVIF
- پشتیبانی از خروجی VGA و HDMI با وضوح تصویر FULL HD

VIDEO CHANNEL INPUT

ANALOG/IP CHANNEL INPUT: 16CH/8CH,(ONLY IP UP TO 16CH)

	AHD	TVI	CVI
Supported Analog Camera Types:	5MP/12fps 4MP/15fps 1080P/30fps 720P/30fps	5MP/12fps 4MP/15fps 1080P/30fps 720P/30fps	1080P/30fps 720P/30fps

Support CVBS input

AUDIO CHANNEL INPUT

Audio Input: 1-ch, RCA

Audio Compression: G.711U

Video/Audio Output

VGA Output: 1920x1080/60Hz

HDMI Output: 1920x1080/60Hz

Audio Output: 1-ch, RCA

Sync Playback: HD: 8-ch/SD: 16-ch

Live view display: HDMI/VGA: 1/4/6/8/9/16/25

Two-way Audio: 1-ch, RCA

Network

Incoming Bandwidth: 40Mbps

Outgoing Bandwidth: 64Mbps

Remote Users: 128

Protocols: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Encoding

Recording Resolution: 5MP Lite/4MP Lite /1080P Lite/720P/CIF

Audio Sample Rate: 8KHz,16 bit per channel

Audio Bit Rate: 64Kbps per channel

Hard Disk

SATA: 1 SATA interface(Up to 8TB for each HDD)

General Alarm

General Alarm: By analog/IP camera: Motion detection

Alert Alarm: IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Running Out of Space, Space Used Up, Recording Abnormal

Smart Function

Intelligent Function: Ultra Motion Detection(UMD) for analog, 8-ch, Behavior Search

Snapshot

FTP/Schedule/Event Snapshot: Schedule snapshot is not supported 16-ch snapshot, up to 704*576 resolution

External Interface

Network Interface: 1RJ45 10M/100M

USB Interface: Rear panel: 2 x USB2.0

Serial Interface: 1 x RS485

power

Power Supply: 12V DC Power Consumption: <10 W(without HDD)

Working Environment: -10°C ~ +55°C

Dimensions(W-D-H): 260mm * 229mm * 47mm (10.2" * 9.0" * 1.8")

Weight: <1.1 Kg (2.42lb) Without HDD

Certification: CE/FCC/WECE

