



- پشتیبانی از فشرده سازی تصویر H.265
- پشتیبانی از پروتکل های ONVIF و RTSP
- پشتیبانی از خروجی VGA و HDMI با وضوح تصویر FULL HD

- ورودی 8 کانال آنالوگ و 4 کانال آی بی
- قابلیت فشرده سازی صدا
- قابلیت صدای دو طرفه

VIDEO CHANNEL INPUT

ANALOG/IP CHANNEL INPUT: 8CH/4CH,(ONLY IP UP TO 8CH)

	AHD	TVI	CVI
	5MP/12fps	5MP/12fps	1080P/30fps
	4MP/15fps	4MP/15fps	
Supported Analog Camera Types:	1080P/30fps	1080P/30fps	720P/30fps
	720P/30fps	720P/30fps	

Support CVBS input

AUDIO CHANNEL INPUT

Audio Input: 1-ch, RCA

Audio Compression: G.711U

Video/Audio Output

VGA Output: 1920x1080/60Hz

HDMI Output: 1920x1080/60Hz

Audio Output: 1-ch, RCA

Sync Playback: HD: 4-ch/SD: 8-ch

Live view display: HDMI/VGA: 1/4/6/8/9/10/16

Two-way Audio: 1-ch, RCA

Network

Incoming Bandwidth: 32Mbps

Outgoing Bandwidth: 64Mbps

Remote Users: 128

Protocols: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Encoding

Recording Resolution: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF

Audio Sample Rate: 8KHz, 16 bit per channel

Audio Bit Rate: 64Kbps per channel

Hard Disk

SATA: 1 SATA interface(Up to 8TB for each HDD)

General Alarm

General Alarm: By analog/IP camera: Motion detection

Alert Alarm: IP Conflict, Network Disconnected, Disk offline
Disk Abnormal, Illegal Access

External Interface

Network Interface: 1RJ45 10M/100M

USB Interface: Rear panel: 2 x USB2.0

power

Power Supply: 12V DC Power Consumption: <8 W(without HDD)

Working Environment: -10°C ~ + 55°C

Dimensions(W-D-H): 260mm * 218mm * 47mm (10.2" * 8.6" * 1.9")

Weight: <1.1 Kg (2.42lb)/Without HDD

Certification: CE/FCC/WECE

