



- پشتیبانی از دوربین های با قابلیت ONVIF
- پشتیبانی از خروجی HDMI با وضوح تصویر 4K

- ورودی 10 کانال آی پی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از فشرده سازی تصویر H.265

VIDEO CHANNEL INPUT

IP CHANNEL INPUT: 10CH x 4K/30fps (Up to 8MP Supported)

AUDIO CHANNEL INPUT

Audio Input: 1-ch, RCA

Audio Compression: G.711U

Video/Audio Output

VGA Output: 1920x1080/60Hz

HDMI Output: 4K(3840x2160)/30Hz

Audio Output: 1-ch, 3.5mm

Sync Playback: 10-ch

Live view display: HDMI/VGA: 1/4/6/8/9/10

Corridor Mode Screen: 3, 4, 5, 7, 9, 10

Video Compression: Ultra 265, H.265, H.264

Network

Incoming Bandwidth: 64Mbps

Outgoing Bandwidth: 32Mbps

Remote Users: 128

Protocols: P2P, UPnP, DHCP

Encoding

Recording Resolution: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Hard Disk

SATA: 1 SATA Interface (Up to 6TB for each HDD)

External Interface

Network Interface: 1 RJ45 10M/100M

USB Interface: Rear panel: 2 x USB2.0

power

Power Supply: 12V DC Power Consumption: < 3 W (without HDD)

Working Environment: -10°C ~ + 55°C

Dimensions (W-D-H): 260mm-243mm-46mm (10.2"-9.6"-1.8")

Weight: < 1Kg (2.2 lb) Without HDD

Certification: CE/FCC/WEEE

