



قابلیت های هوشمند:

- تعقیب سوژه
- تشخیص چهره
- تشخیص عبور از خط
- تشخیص انسان
- نظارت بر تراکم جمعیت
- تشخیص تغییر صحنه
- شیء جامانده
- تشخیص نفوذ
- تشخیص صدا
- شمارش افراد
- شیء حذف شده
- پروتکل SIP توسط IPC

- ورودی 32 کانال آی پی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از فشرده سازی تصویر H.265
- پشتیبانی از دوربین های با قابلیت ONVIF
- پشتیبانی از خروجی HDMI با وضوح تصویر 4K

VIDEO CHANNEL INPUT

IP CHANNEL INPUT: 32CH x 4K/30fps (Up to 8MP Supported)

AUDIO CHANNEL INPUT

Audio Input: 1-ch, RCA

Audio Compression: G.711A, G.711U

Video/Audio Output

VGA Output: 1920x1080/60Hz

HDMI Output: 4K(3840x2160)/30Hz

Audio Output: 1-ch, RCA

Sync Playback: 32-ch

Live view display: HDMI/VGA: 1/4/6/8/9/16/25/36

Two-way Audio: 1-ch, RCA

Corridor Mode Screen: 3,4,5,7,9,10,12,16,32

Video Compression: Ultra 265, H.265, H.264

Network

Incoming Bandwidth: 160Mbps

Outgoing Bandwidth: 64Mbps

Remote Users: 128

Protocols: TCP/IP, P2P, UPnP, NTP, DHCP, PPPOE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP

Encoding

Recording Resolution: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Hard Disk

SATA: 4 SATA interface(Up to 8TB for each HDD)

General Alarm

General Alarm: Motion detection, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection

Alert Alarm:

IP Conflict, Network disconnected, Disk offline, Disk Abnormal, Illegal Access, Running Out of Space, Space Used Up, Recording Abnormal

Smart Function

Intelligent Function: Face detection, Intrusion detection, Cross Line detection, Audio detection, Human body detection, People Counting, People flow Counting, Crowd density monitoring, Scene Change detection, Defocus detection, Auto Tracking, Object Left Behind, Object Removed, SIP by IPC

Intelligent Search: Face Search, Behavior Search

Smart Intrusion Prevention (SIP) by Camera: 8-CH

Snapshot

FTP/Schedule/Event Snapshot: 4-CH SNAPSHOT

External Interface

Network Interface: 2* RJ45 10M/1000M

USB Interface: 1x USB 2.0 x USB 3.0/Front panel: 1x USB2.0

Alarm In: NA

Alarm Out: NA

power

Power Supply: 12V DC Power Consumption: < 15 W(without HDD)

Working Environment: -10°C ~ + 55°C

Dimensions(W*D*H): 440mm*344mm*50mm (2.0" * 13.5" * 1.7")

Weight: < 3.15 Kg (6.94 lb) Without HDD

Certification: CE/FCC/WEEE

