



قابلیت های هوشمند:

- تشخیص چهره
- تشخیص نفوذ
- تشخیص عبور از خط
- تشخیص صدا

- ورودی 16 کانال آی پی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از فشرده سازی تصویر H.265
- پشتیبانی از دوربین های با قابلیت ONVIF
- پشتیبانی از خروجی HDMI با وضوح تصویر 4K

VIDEO CHANNEL INPUT

IP CHANNEL INPUT: 16CH x 4K/30fps (Up to 8MP Supported)

AUDIO CHANNEL INPUT

Audio Input: 1-ch, RCA

Audio Compression: G.711U

Video/Audio Output

VGA Output: 1920x1080/60Hz

HDMI Output: 4K(3840x2160)/30Hz

Audio Output: 1-ch, RCA

Sync Playback: 16-ch

Live view display: HDMI/VGA: 1/4/6/8/9/16

Two-way Audio: 1-ch, RCA

Corridor Mode Screen: 3,4,5,7,9,10,12,16

Video Compression: Ultra 265, H.265, H.264

Network

Incoming Bandwidth: 80Mbps

Outgoing Bandwidth: 80Mbps

Remote Users: 128

Protocols: P2P, UPnP, NTP, DHCP, PPPoE

Encoding

Recording Resolution: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Audio Sample Rate: 8KHz, 16 bit per channel

Audio Bit Rate: 64Kbps per channel

Hard Disk

SATA: 1 SATA interface (Up to 10TB for each HDD)

General Alarm

General Alarm: By analog/IP camera: Motion detection

Alert Alarm: IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Running Out of Space, Space Used Up, Recording Abnormal

Smart Function

Intelligent Function: Face detection, Intrusion detection, Cross line detection, Audio detection

External Interface

Network Interface: 1 RJ45 10M/100M

USB Interface: Rear panel: 2 x USB2.0, Front panel: 1 x USB2.0

Alarm In: 4-ch

Alarm Out: 1-ch

power

Power Supply: 12V DC Power Consumption: < 8 W (without HDD)

Working Environment: -10°C ~ +55°C

Dimensions (W×D×H): 260mm×243mm×46mm (10.2"×9.6"×1.8")

Weight: < 1.12 Kg (2.47 lb) Without HDD

Certification: CE/FCC/WEEE

